

Breitkeilriemen - Umrechnungstabelle

	Riemen- breite oben (mm)	Wirkbreite (mm)	Riemen- breite unten (mm)	Riemen- höhe (mm)	Flanken- winkel (°)	Außenlänge La (mm)	Richtlänge Ld (mm)	Innenlänge Li (mm)	Gewicht (kg/m)
NL = Nennlänge									
17/6 (W 16)	17	1680	14,2	6	26	La = Ld + 10 La = Li + 38	NL	Li = La - 38 Li = Ld - 28	0,113
21/7 (W 20)	21	20	17,5	7	28	La = Ld + 11 La = Li + 44	NL	Li = La - 44 Li = Ld - 33	0,161
22/6	22	21,3	19,2	6	26	La = Ld + 10 La = Li + 38	Ld = Li + 28 Ld = La - 10	NL	0,145
26/8 (W 25)	26	25	22	8	28	La = Ld + 12 La = Li + 50	NL	Li = La - 50 Li = Ld - 38	0,226
28/8	28	27,1	24,3	8	26	La = Ld + 12 La = Li + 50	Ld = Li + 38 Ld = La - 12	NL	0,245
33/10 (W 31,5)	33	31,5	28	10	28	La = Ld + 16 La = Li + 63	NL	Li = La + 63 Li = Ld - 47	0,361
37/10	37	35,7	32	10	28	La = Ld + 16 La = Li + 63	Ld = Li + 47 Ld = La + 16	NL	0,401
42/13 (W 40)	42	40	35,5	13	28	La = Ld + 20 La = Li + 82	NL	Li = La + 82 Li = Ld - 62	0,600
47/13	47	45,4	40,5	13	28	La = Ld + 20 La = Li + 82	Ld = Li + 62 Ld = La + 20	NL	0,675
52/16 (W 50)	52	50	43,4	16	30	La = Ld + 25 La = Li + 100	NL	Li = La + 100 Li = Ld - 75	0,916
55/16	55	53	47	16	28	La = Ld + 25 La = Li + 100	Ld = Li + 75 Ld = La + 25	NL	0,969
65/20 (W 63)	65	63	54,3	20	30	La = Ld + 32 La = Li + 126	NL	Li = La + 126 Li = Ld - 94	1,429
83/26 (W 80)	83	80	68,1	26	32	La = Ld + 41 La = Li + 163	NL	Li = La + 163 Li = Ld - 122	2,366